

(19)



Europäisches Patentamt  
European Patent Office  
Office européen des brevets



(11)

**EP 1 215 632 A2**

(12)

**EUROPEAN PATENT APPLICATION**

(43) Date of publication:  
**19.06.2002 Bulletin 2002/25**

(51) Int Cl.7: **G07C 9/00**

(21) Application number: **01129260.4**

(22) Date of filing: **12.12.2001**

(84) Designated Contracting States:  
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU  
MC NL PT SE TR**  
Designated Extension States:  
**AL LT LV MK RO SI**

(30) Priority: **14.12.2000 JP 2000379793**

(71) Applicant: **Omron Corporation**  
**Kyoto-shi, Kyoto-fu, 600-8530 (JP)**


(72) Inventors:  
• **Tsuyoshi, Fujiwara, c/o Omron Corp., 801  
Shimogyo-ku, Kyoto-shi, Kyoto 600-8530 (JP)**  
• **Yuji, Taketoshi, c/o Omron Corp., 801  
Shimogyo-ku, Kyoto-shi, Kyoto 600-8530 (JP)**  
• **Amehiko, Iki, c/o Omron Corp., 801  
Shimogyo-ku, Kyoto-shi, Kyoto 600-8530 (JP)**

(74) Representative: **Käck, Jürgen**  
**Kahler, Käck, Fiener et Col.**  
**Vorderer Anger 268**  
**86899 Landsberg (DE)**

**(54) Entrance administration equipment and system thereof**

(57) When an entrance administration equipment (1) detects an approaching user, it transmits a communication trigger command to a portable telephone (21), which is owned by the approaching user. When it receives a response signal from the portable telephone (21), it transmits a transmitting command of embarkation person information. When it receives the embarkation person information from the portable telephone (21), it executes an authentication process. When the embarkation person information does not coincide with data of the embarkation-scheduled person database, an entrance administration equipment (1) displays a message of a failure of the authentication process and closes a door (12). When the authentication process is succeeded, the entrance administration equipment (1) records the embarkation person information, opens the door (12), issues a ticket with printed embarkation person information, and transmits a control signal for turning off power of the portable telephone to the portable telephone (21).

**FIG. 1**



**EP 1 215 632 A2**

## Description

## BACKGROUND OF THE INVENTION

## 1. Field of the Invention

[0001] This invention relates to an entrance administration equipment and system. The entrance administration equipment is communicated with a portable communication terminal such as a multifunctional portable telephone, for administering an entrance passed by a user holding the portable communication terminal.

## 2. Description of the Related Art

[0002] Recently, a multifunctional portable telephone reserves seat tickets for a train, an airplane or a music concert. Then multifunctional portable telephone stores reserved information and seat information, instead of the tickets made of paper. The stored information is used for processing entrance or confirming the reserved seat.

[0003] In addition, the number of users of portable telephones increases rapidly, and the use of portable telephones in unfavorable location is a recent social problem.

[0004] For example, the use of a portable telephone in a movie theater or a train gives unpleasant feelings to those around the portable telephone. Besides, the use of a portable telephone close to an electric instrument is likely to invite malfunction of the electric instrument.

[0005] Accordingly, there have been proposed heretofore various systems limiting the use of portable telephones in the location that the use of such portable telephones is unfavorable.

[0006] For example, there has been proposed a system in which any operation of a portable phone is disabled when the phone receives a radio wave transmitted from a device installed in a train or a bus. Then the portable phone is enabled as a user carrying the portable phone goes down from the train or the bus; the radio wave does not reach the portable telephone.

[0007] There has been proposed another system in which a pair of equipments is installed in a predetermined area to limit the use of a portable telephone. A condition of the portable phone turns to enable to call or disable to call according to the order of receiving a radio wave transmitted from each of the equipments.

[0008] Moreover, there has been proposed still another system in which a condition of the portable phone turns to enable to receive or disable to receive according to a switching signal transmitted from an equipment installed in the entrance of an area where the use of the portable phone is limited.

[0009] Also, there has been proposed still another system in which a call of a portable phone is limited by receiving a control signal transmitted from an entrance

wicket of a railway station but only communication by pager transmission mode is enabled.

[0010] In the above-proposed systems, a portable telephone is designed to control to cut power of the portable phone (turned to a power off state) when a user enters into a predetermined location by passing the location where a control device for controlling power of the portable telephone is installed. However, the user has to turn on the power of the portable phone again in order to confirm the stored information such as reserved-seat information of a train or an airplane after entry.

## SUMMARY OF THE INVENTION

[0011] It is, therefore, a primary object of this invention to provide a system in which a portable communication terminal represented by a portable telephone is used for entrance administration in an embarkation entrance of an airport, a wicket of railway, or an entrance of a concert hall or a movie theater. Besides, power of the portable communication terminal is automatically controlled in a location where the use of the portable communication terminal is limited. Then the information necessary after turning off or deactivating the power of the portable communication terminal in the location can be printed on a media such as a predetermined paper without referring to the stored information of the portable communication terminal.

[0012] According to a first aspect of this invention, there is provided an entrance administration equipment which includes a first transmitter for transmitting a transmission command of first information representing visitor information to a portable communication terminal, a receiver for receiving the first information from the portable communication terminal, a determining unit for determining based on the first information received by the receiver whether or not a user carrying the portable communication terminal is allowed to enter, a printer for printing second information on a predetermined media based on the first information received by the receiver when the determining unit determines that the user is allowed to enter, and a second transmitter for transmitting to the portable communication terminal a control signal for cutting or deactivating power of the portable communication terminal.

[0013] The portable communication terminal communicates with other equipment such as a portable telephone, a PDA (Personal Digital (Data) Assistants) or the like.

[0014] For example, the first transmitter, the receiver and the second transmitter are represented by a short-range communication unit. The first transmitter, the receiver and the second transmitter may transmit and receive information by non-contact employing an electromagnetic wave or by electrical contact.

[0015] The first information received by the receiver includes the information for determining in the entrance

administration equipment whether or not a person (user) owning the portable communication terminal is allowed to enter it, and the information for identifying the portable communication terminal. For instance, when the entrance administration equipment is installed in an embarkation entrance of an airport, the entrance administration equipment receives information such as a reservation identification, an airline company name, a flight number, a seat number, an embarkation person full name, a departure schedule time of day, and an arrival schedule time of day about an embarkation-scheduled person, as the first information.

**[0016]** The determining unit determines based on the received first information whether or not a user holding a portable communication terminal is allowed to enter inside of the embarkation entrance of the airport where the entrance administration equipment is installed. In other words, the determining unit determines whether or not a coping embarkation ticket of an airplane is purchased and its corresponding electronic information is stored in the portable communication terminal. For example, the determining unit may be represented by an authentication unit. Also, portable communication terminal may be represented by a portable telephone.

**[0017]** The printer prints the second information on a predetermined media for a user who is allowed to enter by the determining unit. The predetermined media may employ any media on which information can be printed, such as a predetermined size of paper, a plastic card or the like. For example, the printer may be represented by a ticket issuer.

**[0018]** The second information printed by the printer may include an airline company name, a flight number, a seat number, an embarkation person full name, a departure schedule time of day, and an arrival schedule time of day, whereby, for example, a ticket is produced.

**[0019]** For example, the entrance administration equipment is installed in an embarkation entrance of an airport, a wicket of a railway, or an entrance of a concert hall or a movie theater.

**[0020]** In the entrance administration equipment according to the first aspect of this invention, the transmission command of the first information representing visitor information is transmitted to the portable communication terminal. Then the first information is received from the portable communication terminal. Then it is determined based on the received first information whether or not the user carrying the portable communication terminal is allowed to enter. Then the second information is printed on the predetermined media based on the received first information when it is determined that the user is allowed to enter. Then the control signal for cutting power of the portable communication terminal is transmitted to the portable communication terminal.

**[0021]** Therefore, at the location where the portable communication terminal is used for an entrance administration and the use of the portable communication terminal is limited, the power of the portable communication

terminal is automatically controlled, thereby suppressing unpleasant feelings given to others and preventing any emission of radio waves causing malfunction of other precision instruments. Furthermore, the information necessary after power deactivation of the portable communication terminal is printed on the media such as a predetermined paper, so that the user is not required to activate the power of the portable communication terminal again for referring to the information.

**[0022]** In addition, the second information may include the information necessary after cutting the power of the portable communication terminal, which is included in the first information.

**[0023]** The first information includes a reservation's identification, an airline company name, a flight number, a seat number, an embarkation person full name, a departure schedule time of day, an arrival schedule time of day and so on about an embarkation-scheduled person or passenger. For example, the information necessary after cutting or deactivating the power of the portable communication terminal includes the seat number and the arrival schedule time of day to be confirmed when the passenger seats. However, the reservation identification is not necessary to be referred by the passenger, and it is conceivable that reference to an airline company name is not necessary inside of an embarkation entrance where the embarkation entrance is isolated for each airline company.

**[0024]** Since the second information includes the information in the first information that is necessary after cutting the power of the portable communication terminal, all of the received first information is not printed but only the second information necessary for the passenger is printed, thereby miniaturizing in size the media made of paper or the like.

**[0025]** The first information and the second information may include the seat number.

**[0026]** The seat number in an airplane is not necessary in order to process entrance operations at the embarkation entrance, but is necessary for the passenger to enter the embarkation entrance and take the reserved seat in the airplane for confirmation. By including a seat number in the first and second information, the seat number can be written on the medium to be printed (for example, a ticket), thereby providing passengers with convenient service.

**[0027]** The predetermined medium may employ a predetermined media made of paper.

**[0028]** In addition, there can be provided a notifying unit for notifying that a passenger or user is not allowed to enter.

**[0029]** The notifying unit may display a message such that the user is not allowed to enter, whereby the user is notified that entrance of the user is not allowed.

**[0030]** For example, the notifying unit may be represented by a display unit which displays the message, such as "PLEASE ENSURE YOUR ENTRANCE GATE", "PLEASE TURN AROUND AISLE ATTENDED

BY PERSON IN CHAGRE" and the like on, when the user is not allowed to enter, thereby notifying the user that entrance of the user is not allowed.

[0031] The notifying unit may be designed to produce a voice signal showing that the user is not allowed to enter, whereby the user is notified that entrance of the user is not allowed.

[0032] The voice signal for notifying that the user is not allowed to enter can include a voice message, such as "PLEASE ENSURE YOUR ENTRANCE GATE", "PLEASE TURN AROUND AISLE ATTENDED BY PERSON IN CHAGRE" and the like, in addition to buzzer or alarm.

[0033] When a user is not allowed to enter, the notifying unit may be designed to notify by activating or deactivating a predetermined LED that the user is not allowed to enter.

[0034] Other than the case that activating or deactivating the predetermined LED indicates that the user going to pass the entrance administration equipment is not allowed to enter, LEDs of different colors can be illuminated whether the user is allowed to enter or not.

[0035] Employment of thus notifying unit can provide a user or an entrance managing administrator with a comprehensive notice such as whether a user going to pass the entrance administration equipment is allowed to enter or not.

[0036] Further, there may be provided a controlling unit for controlling opening and closing of a predetermined member to limit pass of users, which controls opening and closing of the predetermined member based on determination results by the determining unit.

[0037] For example, the controlling unit may be represented by a door driver unit. The predetermined member for limiting pass of users may be represented by a door at entrance.

[0038] When it is determined that a user going to pass the entrance administration equipment is not allowed to enter, the door driver unit closes the door so that the user cannot enter. When it is determined that the user is allowed to enter, the door driver unit opens the door so that the user can enter. Thus, passage of users can be limited based on the determination results whether or not a user can enter.

[0039] The entrance administration equipment may further include a storing unit for storing information with respect to a user who is allowed to enter, in which the determining unit can refer to information with respect to the user stored by the storing unit and determine whether or not the user carrying the portable communication terminal is allowed to enter.

[0040] For example, the storing unit may be represented by an embarkation-scheduled person database unit. The information with respect to a user who is allowed to enter may be represented by embarkation person information of a reservation identification of an embarkation-scheduled person or passenger. An authentication unit can determine whether or not a user who

holds a portable communication terminal is allowed to enter by determining whether or not the inputted embarkation person information coincides with information stored in the embarkation-scheduled person database unit. Accordingly, it can be determined by referring to information stored beforehand whether or not a user who holds a portable communication terminal is allowed to enter.

[0041] The entrance administration equipment may further include a recording unit for recording the information of the user who is determined to be able to enter by the determining unit.

[0042] For example, the recording unit may be represented by a visitors recording unit. Embarkation person information of a user who is authenticated by the authentication unit to enter inside of the entrance administration equipment is recorded in the visitors recording unit.

[0043] By recording the information about the user determined to be able to enter, the user entered inside can be confirmed. For example, it can be confirmed whether or not an embarkation procedure of all embarkation scheduled persons is finished.

[0044] According to a second aspect of this invention, there is provided an entrance administration equipment which includes a first transmitter for transmitting a transmission command of first information representing visitor information to a communication terminal, a receiver for receiving the first information from the portable communication terminal, a determining unit for determining based on the first information received by the receiver whether or not a user carrying the portable communication terminal is allowed to enter, a printer for printing second information on a predetermined media based on the first information received by the receiver when the determining unit determines that the user is allowed to enter, and a second transmitter for transmitting to the portable communication terminal a control signal for cutting or deactivating power of a communication function of the portable communication terminal.

[0045] The portable communication terminal is a terminal, which can communicate with other equipment such as a portable telephone, a PDA (Personal Digital (Data) Assistants) or the like.

[0046] For example, the first transmitter, the receiver and the second transmitter may be represented by a short-range communication unit. The first transmitter, the receiver and the second transmitter may transmit and receive information by non-contact with electromagnetic waves or by electrical contact.

[0047] The first information received by the receiver includes the information for determining in the entrance administration equipment whether or not a user owning the portable communication terminal is allowed to enter, and the information for identifying the portable communication terminal. For instance, when the entrance administration equipment is installed in an embarkation entrance of an airport, the entrance administration

equipment receives information as the first information, such as a reservation identification, an airline company name, a flight number, a seat number, an embarkation person full name, a departure schedule time of day, an arrival schedule time of day about an embarkation-scheduled person.

**[0048]** For example, the determining unit may be represented by an authentication unit. The determining unit determines based on the received first information whether or not the user holding the portable communication terminal such as the portable telephone can enter inside of the embarkation entrance of the airport where the entrance administration equipment is installed. In other words, the determining unit determines whether or not an embarkation ticket of a coping airplane is purchased and its corresponding electronic information is stored in the portable communication terminal.

**[0049]** For example, the printer may be represented by a ticket issuer. The printer prints the second information on a predetermined media for a user who is determined by the determining unit to be allowed to enter. The predetermined media may employ any media on which information can be printed, such as a predetermined size of a paper, a plastic card or the like.

**[0050]** The second information printed by the printer may include an airline company name, a flight number, a seat number, an embarkation person full name, a departure schedule time of day, and an arrival schedule time of day, whereby, for example, a ticket is made.

**[0051]** For example, the entrance administration equipment including these components is installed in an embarkation entrance of an airport, a wicket of a railway, or an entrance of a concert hall or a movie theater.

**[0052]** The second transmitter produces a control signal for cutting power of a communication function in the functions employed in the portable communication terminal to be transmitted to the portable communication terminal.

**[0053]** In the entrance administration equipment according to the second aspect of this invention, the transmission command of the first information representing visitor information is transmitted to the portable communication terminal, the first information is received from the portable communication terminal, it is determined based on the received first information whether or not the user carrying the portable communication terminal is allowed to enter. The second information is printed on the predetermined media based on the received first information when it is determined that the user is allowed to enter. The control signal for cutting power of the communication function of the portable communication terminal is transmitted to the portable communication terminal.

**[0054]** Therefore, the power of the communication function of the portable communication terminal at the location where the use of the portable communication terminal is limited is automatically controlled, thereby suppressing unpleasant feelings given to other people

and preventing emission of radio wave causing malfunction of other precision instrument while other function of the portable communication terminal than the communication function is activated. Furthermore, the information necessary after power deactivation of the portable communication terminal is printed on a media such as a predetermined paper, so that the user is not needed to activate the power of the portable communication terminal again for referring to this information.

**[0055]** An entrance administration system according to this invention includes an entrance administration equipment and a portable communication terminal. The entrance administration equipment includes a first transmitter for transmitting a transmission command of first information representing visitor information to the communication terminal, a first receiver for receiving the first information from the portable communication terminal, a determining unit for determining based on the first information received by the first receiving unit whether or not the user carrying the portable communication terminal is allowed to enter, a printer for printing second information on a predetermined media based on the first information received by the first receiving unit when the determining unit determines that the user is allowed to enter, and a second transmitter for transmitting to the portable communication terminal a control signal for cutting power of the portable communication terminal. The portable communication terminal includes a storing unit for storing the first information, a second receiver for receiving a transmission command of the first information stored in the storing unit from the entrance administration equipment, a third transmitter for transmitting the first information stored in the storing unit, a third receiver for receiving the control signal for controlling the power from the entrance administration equipment, and a controller for controlling the power based on the control signal received by the third receiver.

**[0056]** The portable communication terminal communicates with other equipment such as a portable telephone, a PDA (Personal Digital (Data) Assistants) or the like.

**[0057]** For example, the first transmitter, the first receiver and the second transmitter may be represented by a short-range communication unit. The first transmitter, the first receiver and the second transmitter may transmit and receive information by non-contact with electromagnetic waves or by electrical contact.

**[0058]** The first information received by the first receiver includes, for example, a reservation identification, an airline company name, a flight number, a seat number, an embarkation person full name, a departure schedule time of day, an arrival schedule time of day about an embarkation-scheduled person.

**[0059]** For example, the determining unit may be represented by an authentication unit. The determining unit determines based on the received first information whether or not the user holding the portable communication terminal such as the portable telephone is al-

lowed to enter inside of the embarkation entrance of the airport where the entrance administration equipment is installed. In other words, the determining unit determines whether an embarkation ticket of a coping airplane is purchased and its corresponding electronic information is stored in the portable communication terminal.

**[0060]** For example, the printer may be represented by a ticket issuer. The printer prints the second information on a predetermined media for a user who is allowed to enter by the determining unit. The predetermined media may employ any media on which information can be printed, such as a predetermined size of paper, a plastic card or the like.

**[0061]** The second information printed by the printer may include an airline company name, a flight number, a seat number, an embarkation person full name, a departure schedule time of day, and an arrival schedule time of day, whereby, for example, a ticket is made.

**[0062]** For example, the entrance administration equipment provides with these components is installed in an embarkation entrance of an airport, a wicket of a railway, or an entrance of a concert hall or a movie theater.

**[0063]** For example, the storing unit is represented by a storage section. The storage section stores therein the first information including a reservation identification, an airline company name, a flight number, a seat number, an embarkation person full name, a departure schedule time of day, an arrival schedule time of day about an embarkation-scheduled person, to be transmitted to the entrance administration equipment, if desired.

**[0064]** For example, the second receiver, the third transmitter and the third receiver may be represented by a short-range communication unit. The short-range communication unit receives a transmission command of the first information stored in the storing unit from the entrance administration equipment and transmits the first information stored in the storing unit, and receives a control signal for controlling power from the entrance administration equipment.

**[0065]** The controller, for example, is represented by a power supply control unit. The power supply control unit controls the power of a call unit based on the control signal received by the short-range communications unit.

**[0066]** In the entrance administration system according to this invention, the entrance administration equipment transmits a transmission command of the first information representing visitor information to the portable communication terminal, receives the first information to determine based on the received first information whether or not the user carrying the portable communication terminal is allowed to enter, and, when it is determined that the user is allowed to enter, prints the second information on the predetermined media based on the received first information, and transmits to the portable communication terminal the control signal for cutting power of the portable communication terminal, while the

portable communication terminal storing the first information therein, receives the transmission command of the stored first information, transmits the first information, receives the control signal for controlling power, and controls the power based on the received control signal.

**[0067]** Therefore, at the location where the portable communication is used for an entrance administration and the use of the portable communication terminal is limited, the power of the portable communication terminal is automatically controlled, thereby suppressing unpleasant feelings given to others and preventing emission of radio wave causing malfunction of other precision instrument. Furthermore, the information necessary after power deactivation of the portable communication terminal is transmitted from the portable communication terminal to the entrance administration equipment, and printed on a media such as a predetermined paper in the entrance administration equipment, so that the user is not needed to activate the power of the portable communication terminal again for referring to these information.

#### BRIEF DESCRIPTION OF THE DRAWINGS

**[0068]** Other objectives and advantages of this invention will be more readily apparent from the following detailed description provided in conjunction with the following figures, of which:

Fig. 1 is a perspective view of an entrance administration system according to a preferred embodiment of this invention;

Fig. 2 is a block diagram showing an internal construction of an entrance administration equipment employed in the system of Fig. 1;

Fig. 3 is a block diagram showing a construction of a short-range communication unit employed in the equipment of Fig. 2;

Fig. 4 shows an example of a ticket issued from the entrance administration equipment of Fig. 1;

Fig. 5 is a block diagram showing an internal construction of a portable telephone employed in the system of fig. 1;

Fig. 6 shows a flow chart for an operation in the entrance administration equipment; and

Fig. 7 is a flow chart for an operation in the portable telephone.

#### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

**[0069]** Fig.1 depicts an entrance administration system according to a preferred embodiment of this invention, which includes an entrance administration equipment 1 and a portable telephone 21.

**[0070]** The entrance administration equipment 1 may be installed at an embarkation entrance of an airplane,

a wicket of a station, an entrance of a movie theater or a concert hall, or the like, to execute an entrance procedure. In this embodiment, the entrance administration equipment 1 is installed at an embarkation entrance of an airplane.

**[0071]** When a user or passenger enters the entrance installed by the entrance administration equipment 1 to stay in a area administrated thereby, the passenger brings the portable telephone 21 close to a short-range communication unit 11 disposed on an upper wall of the entrance administration equipment 1 to communicate with the entrance administration equipment 1 for transmitting embarkation person information stored in the portable telephone 21 to the entrance administration equipment 1, thereby executing an entrance procedure.

**[0072]** In Fig. 1, the location on which the passenger stands is an aisle. As a door 12 opens, the passenger can pass through the aisle to enter into an appointed area.

**[0073]** Furthermore, as the passenger has entered through the embarkation entrance, the entrance administration equipment 1 transmits a control signal to control power supply of a whole part of the portable telephone 21 or a part executing a call function thereof to limit speaking over the portable telephone 21.

**[0074]** When the above-described entrance procedure is finished, the entrance administration equipment 1 transmits a control signal for disconnecting (power off) power of the portable telephone 21 from the short-range communication unit 11. Then the portable telephone 21 turns off its power supply upon receiving the control signal.

**[0075]** Furthermore, the entrance administration equipment 1 prints the information such as a seat number necessary after power-off on a media of a card type to be issued from a ticket issuer 13.

**[0076]** The ticket issuer 13 is disposed at a back or near an exit of the aisle formed by the entrance administration equipment 1. The short-range communication unit 11 is disposed near an entry of the aisle. The passenger goes to the back from a front side of the aisle, whereby communication between the short-range communication unit 11 of entrance administration equipment 1 and the portable telephone 21 is carried out at the entry of the aisle. Then a ticket is issued near the exit of the aisle from the ticket issuer 13 along the travel by the passenger. Therefore, the passenger goes smoothly through the aisle made by the entrance administration equipment 1.

**[0077]** Thus, in an entrance of a place such as an inside of an airplane where telephone call with the portable telephone 21 of the is undesirable, the power supply of the portable telephone 21 is controlled to limit its use, whereby an erroneous operation of a component is prevented and unpleasant feelings to others is depressed. Moreover, the information such as a seat number necessary after cutting the power supply of the portable telephone 21 is printed, so that the power of the portable

telephone 21 is not necessary to be reactivated in order to confirm the seat number.

**[0078]** Fig.2 is a block diagram showing an example of an internal construction of the entrance administration equipment 1. The parts corresponding to those in Fig. 1 are given the same reference symbols, and its explanation is omitted for simplification.

**[0079]** A controlling unit 32 controls each unit of the entrance administration equipment 1. The controlling unit 32 makes an order for transmitting embarkation person information to the portable telephone 21 to be transmitted to the portable telephone 21 through a bus 34 and short-range communication unit 11, and outputs the embarkation person information entered through the short-range communication unit 11 to be applied to an authentication unit 31 through the bus 34. Upon receiving an input of an authentication result showing that the passenger is a right embarkation-scheduled person from the authentication unit 31, the controlling unit 32 further generates a control signal for cutting or turning-off the power supply of the portable telephone 21 held by the passenger to be transmitted to the portable telephone 21 through the bus 34. Then the controlling unit 32 outputs the entered embarkation person information to be applied to visitors recording unit 36 and ticket issuer 13 through the bus 34.

**[0080]** An authentication unit 31 refers to an embarkation scheduled person information recorded in an embarkation-scheduled person database 35 on the basis of the embarkation person information inputted by the controlling unit 32 through the bus 34. Then the authentication unit 31 executes an authentication process to determine whether or not the passenger who is going to enter is a right embarkation-scheduled person. Then the authentication unit 31 outputs an authentication result to be applied to controlling unit 32 and door driver 39 through bus 34.

**[0081]** For example, a display 33 employs an LCD (Liquid Crystal Display). The display 33 is disposed on the same wall (top wall of the entrance administration equipment 1) as the wall installed by the short-range communication unit 11 of Fig. 1. The display 33 displays various messages (such as "PLEASE ENSURE YOUR ENTRANCE GATE", "PLEASE TURN AROUND AISLE ATTENDED BY PERSON IN CHARGE" and the like) to the passenger based on the authentication result produced by authentication unit 31 through bus 34.

**[0082]** The short-range communication unit 11 produces an electromagnetic wave to communicate with the portable telephone 21. Fig.3 is a block diagram showing a detailed construction of the short-range communication unit 11.

**[0083]** The short-range communication unit 11 includes a controller 51, a modulator 52, a demodulator 53 and a resonance circuit 54 consisting of a coil 54A and a capacitor 54B.

**[0084]** The controller 51 controls a whole operation of the short-range communication unit 11 based on the sig-

nal entered by the controlling unit 32 through the bus 34. Also the controller 51 applies the information entered by the demodulator 53 to the controlling unit 32 through the bus 34.

**[0085]** The modulator 52 modulates a signal entered by the controller 51 to be supplied to the resonance circuit 54 for emitting an electromagnetic wave to the portable telephone 21 from the coil 54A.

**[0086]** The demodulator 53 demodulates an electromagnetic wave which is transmitted from a short-range communication unit 21 B of the portable telephone 21 (see Fig. 5 described later) and received by the coil 54A serving as an antenna, and applies the demodulated signal to the controller 51.

**[0087]** The resonance circuit 54 is regulated by the coil 54A and the capacitor 54B, and executes resonance at a predetermined resonance frequency to transmit and receive various information by unit of electromagnetic waves communicated with the short-range communication unit 21 B of the portable telephone 21.

**[0088]** Description returns to Fig. 2.

**[0089]** The embarkation-scheduled person database 35 records therein embarkation person information such as reservation identifications of embarkation-scheduled persons. The recorded information is read out by the authentication unit 31 upon requirement. The visitors recording unit 36 receives embarkation person information of the passenger whose authentication is done justly from the controlling unit 32 through the bus 34, and records the embarkation person information. The embarkation-scheduled person database 35 and the visitors recording unit 36 may be represented by an external device disposed outside of the entrance administration equipment 1, if desired.

**[0090]** A passerby detecting unit 37 detects based on a signal produced from a sensor 38 whether or not there exists a passenger near the entrance administration equipment 1, and applies the determination result to the door driver 39 through the bus 34.

**[0091]** The door driver 39 controls opening and closing of the door 12 based on the authentication result applied by the authentication unit 31 and the determination result entered by the passerby detecting unit 37.

**[0092]** The ticket issuer 13, for example, includes a paper tray for accommodating predetermined papers to be printed with information such as seat numbers which is necessary after cutting power of the portable telephone 21, a paper conveyance section for conveying papers from the paper tray, a printer section for printing predetermined information on the papers conveyed from the paper conveyance section. The ticket issuer 13 prints the information necessary after cutting the power of the portable telephone 21 on predetermined paper based on the embarkation person information input by the controlling unit 32, and exhausts the printed paper. A ticket 60 exhausted by the ticket issuer 13 is shown in Fig. 4. The ticket 60 on a single face or both faces thereof is printed with an airline company name, a flight

number, a seat number, an embarkation person full name, departure schedule time of day, arrival schedule time of day, and so on.

**[0093]** Fig. 5 is a block diagram, which shows an example of internal construction of the portable telephone 21.

**[0094]** The portable telephone 21 includes call unit 21A for carrying out an original communication function of a portable telephone, short-range communication unit 21B for carrying out an communication function with the entrance administration equipment 1, and a power supply control unit 21 C. The call unit 21A carries out various processes in a voice call transmission mode and a data communication mode.

**[0095]** A main controller 61 includes a CPU (Central Processing Unit), a ROM (Read Only Memory), and a RAM (Random Access Memory), and controls the respective components connected with a bus 62 in a voice call transmission mode and a data communication mode.

**[0096]** A memory 63 employs a nonvolatile flash memory, and stores various information therein. For example, telephone numbers of other telephones entered through an input section 70 by a user of the portable telephone 21 are administrated and stored as a telephone book. The memory 63 stores mails that have been transmitted and received in data communication mode.

**[0097]** A voice CODEC 64 encodes in a predetermined formula an analog audio signal of a voice collected by a microphone 65 in the voice call mode to be converted into digital sound data. In addition, the voice CODEC 64 decodes in a predetermined formula the digital sound data supplied by a demodulator 68 to be converted into an analog audio signal for application to a speaker 66 to generate a voice.

**[0098]** A modulator 67 executes a spread spectrum process of the supplied digital data, and applies the executed digital data to a communicator 69. For example, the modulator 67 in the voice call mode executes a spread spectrum process of the voice data supplied from the voice CODEC 64 to be supplied to the communicator 69. The modulator 67 in the data communication mode executes a spread spectrum process of the text data entered from the input section 70 to be supplied to the communicator 69.

**[0099]** The communicator 69 executes a digital-to-analog conversion process and a frequency conversion process about the digital data supplied from modulator 67 to be transmitted to the nearest base station (not shown in drawings) through the antenna 69A.

**[0100]** In addition, the communicator 69 executes a frequency conversion process and an analog-to-digital conversion process about the signal received by the antenna 69A, and applies the converted digital data to the demodulator 68.

**[0101]** The demodulator 68 executes a reverse spread spectrum process about the digital data supplied



from the communicator 69 to be supplied to the respective sections. For example, the demodulator 68 in the voice call mode supplies the digital data produced by executing the reverse spread spectrum process to the voice CODEC 64. The demodulator 68 supplies the obtained text data to a display 71 in the data communication mode.

**[0102]** The input section 70 is represented by a numerical keypad or various kinds of switch buttons, and operated by a user.

**[0103]** The display 71 is represented by an LCD or the like, and displays characters and images corresponding to the supplied various data.

**[0104]** When there exists the portable telephone 21 near the short-range communication unit 11 of the entrance administration equipment 1, the short-range communication unit 21B communicates with the short-range communication unit 11.

**[0105]** The short-range communication unit 21 B has a similar construction to that of the short-range communication unit 11 (Fig. 3) of the entrance administration equipment 1. The short-range communication unit 21 B includes a controller 81, a modulator 82, a demodulator 83, and a resonance circuit 85 consisting of a coil 85A and a capacitor 85 B. These components have same functions as those of the controller 51, the modulator 52, the demodulator 53 and the resonance circuit 54 in the short-range communication unit 11, and its explanation is omitted for simplification. The controller 81, however, includes a storage section 81A consisting of a flash memory built therein.

**[0106]** The storage section 81A stores therein embarkation person information such as a reservation identification assigned to a passenger on reserving an aviation ticket, an airline company name, a flight number, a seat number, an embarkation person name, the departure schedule time or the arrival schedule time, which are reserved. The embarkation person information is received from a website administrated by an airline company or other agents through a network such as an internet when an aviation ticket is reserved by using the portable telephone 21, and entered into the main controller 61 to be stored therein.

**[0107]** The short-range communication unit 21B further includes a power supplier 84. The power supplier 84 supplies controller 81, modulator 82 and demodulator 83 with power generated by receiving the electromagnetic wave transmitted from the short-range communication unit 11 of the entrance administration equipment 1 to activate controller 81, modulator 82 and demodulator 83.

**[0108]** Accordingly, the entrance administration equipment 1 can drive the controller 81 by transmitting the electromagnetic wave to the portable telephone 21 in the condition that the portable telephone 21 is cut off its power supply or deactivated.

**[0109]** A power supply control unit 21 C starts to supply electric power from a built-in battery pack when a

power button PW is turned ON for activating the call unit 21A.

**[0110]** The power supply control unit 21C controls the power supply to the call unit 21A by changing the power button PW into ON-or-OFF according to a command from the short-range communication unit 21 B (controller 81). For example, when a control signal designating that the power is cut (deactivated or turn to OFF) is transmitted from the short-range communication unit 11 of the entrance administration equipment 1, the controller 81 of the short-range communication unit 21B instructs the power supply control unit 21 C to cease its supply to the call unit 21A (deactivate call).

**[0111]** When the portable telephone 21 includes functions (data processing functions such as a word processing function or an image processing function) which is different from the communication function, the power supply control unit 21 C can be designed to cut (or deactivate) whole power of the portable telephone 21 or power of one of the functions (for example, only the power for the call unit 21A is cut (or deactivated) but the power for other functions is not cut) based on the command from the short-range communication unit 21B (controller 81).

**[0112]** Referring to a flow chart shown in Fig. 6, an operation executed by the entrance administration equipment 1 will be described hereinafter.

**[0113]** In a step S1, the controlling unit 32 of the entrance administration equipment 1 determines if a passenger approaches on the basis of a signal supplied by the passerby detecting unit 37 through the bus 34. When it is determined in the step S1 that the passenger does not approach, the sequence of the step S1 will be repeated until any passenger is determined to approach.

**[0114]** When it is determined that the passenger approaches in the step S1, the controlling unit 32 generates a control signal for closing the door 12 to be applied to the door driver 39 through the bus 34 in a step S2. The door driver 39 closes the door 12 according to the applied control signal.

**[0115]** In a step S3, the controlling unit 32 generates a control signal for transmitting a communication trigger command to be applied to the short-range communication unit 11. The controller 51 of the short-range communication unit 11 controls the modulator 52 in correspondence with the command applied from the controlling unit 32 to constantly (cyclically at predetermined intervals (for example, interval of several milliseconds) which are short enough in comparison with the movement of a person) transmit the communication trigger command by employing an electromagnetic wave of a predetermined frequency from the resonance circuit 54. The controlling unit 32 waits until it receives a response from the portable telephone 21.

**[0116]** As the passenger brings the portable telephone 21 close to the short-range communication unit 11, the resonance circuit 85 of the portable telephone 21 detects an electromagnetic wave from the coil 54A

of the short-range communication unit 11 to output the detection signal to the demodulator 83. The demodulator 83 demodulates the detection signal to apply a result of the modulation to the controller 81. Then, the controller 81 controls the modulator 82 to modulate a response signal. The response signal is transmitted from the coil 85A of the resonance circuit 85 to the short-range communication unit 11.

**[0117]** Upon receiving an electromagnetic wave corresponding to the response signal from the portable telephone 21, the resonance circuit 54 of the short-range communication unit 11 applies the detected signal to the demodulator 53 to be demodulated. Upon receiving an input of a demodulated signal from the demodulator 53, the controller 51 applies its corresponding response signal to the controlling unit 32 through the bus 34.

**[0118]** In a step S4, the controlling unit 32 determines on the basis of signal entered from the short-range communication unit 11 through bus 34 whether or not the response signal corresponding to the communication trigger command is received. When it is determined that any response signal is not received in the step S4, the sequence returns to the step S3, and its subsequent sequence is repeated.

**[0119]** When it is determined that the response signal is received in the step S4, the controlling unit 32 generates a transmission command of embarkation person information to be transmitted to the portable telephone 21 through the bus 34 and the short-range communication unit 11 in a step S5.

**[0120]** In a step S6, the controlling unit 32 determines on the basis of a signal entered from the short-range communication unit 11 through the bus 34 whether or not embarkation person information is received. When it is determined that any embarkation person information is not received in the step S6, the sequence returns to the step S3, and its subsequent sequence is repeated.

**[0121]** When it is determined that embarkation person information is received in the step S6, the controlling unit 32 outputs the received embarkation person information to be applied to the authentication unit 31 in a step S7. The authentication unit 31 carries out an authentication process on the basis of the embarkation person information entered from the controlling unit 32.

**[0122]** In a step S8, the authentication unit 31 determines whether the entered embarkation person information coincides with data recorded in the embarkation-scheduled person database 35.

**[0123]** When it is determined that the entered input embarkation person information does not coincide with the data recorded in the embarkation-scheduled person database 35 in the step S8, the authentication unit 31 outputs a signal representing a failure of authentication to be applied the controlling unit 32 in step S9. Then, the controlling unit 32 generates a control signal for making the display 33 displays a message showing the failure of authentication to be applied to the display 33.

According to the control signal, the display 33 displays a message showing the failure of authentication (for example, "PLEASE ENSURE YOUR ENTRANCE GATE" and "PLEASE TURN AROUND AISLE ATTENDED BY PERSON IN CHAGRE"). Then the operation ends.

**[0124]** The display 33 of this embodiment displaying a picture message showing the failure of authentication may be modified by employing a speaker in the entrance administration equipment 1 which outputs an alarm sound or a voice message showing the failure of authentication "PLEASE ENSURE YOUR ENTRANCE GATE" and "PLEASE TURN AROUND AISLE ATTENDED BY PERSON IN CHAGRE". Also, the display 33 may be modified by employing an LED in the entrance administration equipment 1 which is activated when the authentication fails. Also, the display 33 may be modified by transmitting a signal representing an error message to the portable telephone 21 through the bus 34 and the short-range communication unit 11 to display the error message on the display 71 of the portable telephone 21.

**[0125]** Activation of the LED shows that the passenger going to pass is not allowed to enter. If desired, however, there may be employed a predetermined LED that is activated when the authentication is carried out correctly and deactivated when the authentication is failed, or different color LEDs which are respectively activated due to allowed to enter or not allowed to enter.

**[0126]** When it is determined that the embarkation person information received from the portable telephone 21 coincides with data recorded in the embarkation-scheduled person database 35 in the step S8, the authentication unit 31 outputs a signal represent that the authentication is normally processed to be applied to the controlling unit 32. The controlling unit 32 generates a control signal for making the visitors recording unit 36 record embarkation person information thereon to be applied to the visitors recording unit 36. The visitors recording unit 36 records the embarkation person information according to the outputted control signal.

**[0127]** In a step S11, the authentication unit 31 outputs a signal represent that the authentication is normally processed, to be applied to the door driver 39. The door driver 39 opens the door 12 in order to allow the passenger to enter.

**[0128]** In a step S12, the controlling unit 32 outputs the embarkation person information to be applied to the ticket issuer 13 through the bus 34. The ticket issuer 13 prints the embarkation person information on a predetermined paper to issue the ticket 60 shown in Fig. 4.

**[0129]** In a step S13, the controlling unit 32 generates a control signal for cutting power supply of the portable telephone 21 to be transmitted to the portable telephone 21 through the bus 34 and the short-range communication unit 11. The operation ends.

**[0130]** When the portable telephone 21 has a different function other than the communicator function, the controlling unit 32 may be modified to generate a control signal for cutting power supply of the call function of the

portable telephone 21 to be transmitted to the portable telephone 21 through the bus 34 and the short-range communication unit 11.

[0131] Next, an operation of the portable telephone 21 will be described hereinafter referring to a flow chart shown in Fig. 7. The operation of the portable telephone 21 is executed concurrently with the operation of the entrance administration equipment 1 explained referring to Fig. 6.

[0132] In a step S21, the controller 81 determines on the basis of a signal entered through the resonance circuit 85 and the demodulator 83 whether the communication trigger command transmitted by the entrance administration equipment 1 in the step S3 of Fig. 6 is received or not. When it is determined that the communication trigger command is not received in the step S21, the sequence of the step S21 is repeated until it is determined that the communication trigger command is received.

[0133] When it is determined that the communication trigger command is received in the step S21, the controller 81 transmits a response signal corresponding to the communication trigger command to the entrance administration equipment 1 through the modulator 82 and the resonance circuit 85 in a step S22.

[0134] In a step S23, the controller 81 determines on the basis of the signal entered by the demodulator 83 whether the transmitting command of the embarkation person information transmitted by the entrance administration equipment 1 in the step S5 of Fig. 6 is received or not. When it is determined that the transmitting command of the embarkation person information is not received in the step S23, the sequence of the step S23 is repeated until it is determined that the emission command of the embarkation person information is received.

[0135] When it is determined that the transmitting command of the embarkation person information is received in the step S23, the controller 81 reads out embarkation person information from the storage section 81A to be transmitted to the entrance administration equipment 1 through the modulator 82 and the resonance circuit 85 in a step S24.

[0136] In a step S25, the controller 81 determines on the basis of a signal entered by the demodulator 83 whether the control signal for cutting the power supply of the portable telephone 21 transmitted by the entrance administration equipment 1 in the step S13 of Fig. 6 is received or not.

[0137] When it is determined that the control signal for cutting the power of the portable telephone 21 is not received in the step S25, the operation ends. Then, if the entrance administration equipment 1 is designed to transmit to the portable telephone 21 a signal corresponding to an error message representing a failure of the authentication, the controller 81 outputs a signal corresponding to the error message entered by the demodulator 83 to be applied to the main controller 61. Then,

the main controller 61 may output the error message to be applied to the display 71 through the bus 62 to be displayed.

[0138] When it is determined that the control signal for cutting the power supply is received in the step S25, the controller 81 controls the power supply control unit 21 C based on the received control signal to cut the power supply which is supplied to the call unit 21A in a step S26, and the sequence finishes.

[0139] When the portable telephone 21 has a function other than the communicator function and the control signal transmitted by the entrance administration equipment 1 is the control signal for cutting the power supply of the portable telephone 21, the controller 81 controls the power supply control unit 21 C based on the received control signal to cut the power supply which is supplied to the call unit 21A but not to cut any power of other function (not shown in drawings).

[0140] Thus, the entrance administration equipment 1 installed in an entrance gate at an embarkation entrance of an airport is designed to communicate with the portable telephone 21 for mutual communication of information, thereby executing an entrance process. When a passenger enters inside of the entrance administration equipment 1, the power of the portable telephone 21 is automatically cut but the information such as a seat number necessary after cutting the power of the portable telephone 21 is printed on a media such as a predetermined paper, so that the passenger is free from turning-on again power of the portable telephone 21 inside of the entrance administration equipment 1.

[0141] Though the entrance administration equipment 1 is installed in the entrance gate of the embarkation entrance of airport in this embodiment, this invention can be applied to an entrance administration equipment installed in a wicket of a railway, an entrance of a concert hall, a movie theater, a hospital or a meeting room, or an exit administration equipment for such facilities.

[0142] Though the embarkation person information stored beforehand in the portable telephone 21 is printed on the ticket 60 in this embodiment, it can be printed on other media such as a plastic card than the media made of paper.

[0143] Though the communication of information between the entrance administration equipment 1 and the portable telephone 21 is executed with non-contact by using electromagnetic waves in this embodiment, it may be executed by employing electric contact terminals for mutual communication therebetween with electric contact.

[0144] The device for communicating with the entrance administration equipment 1 is represented by the portable telephone 21 in this embodiment, but may be represented by other communication terminal such as a PHS (Personal Handy Phone), a PDA (Personal Digital (Data) Assistants) or the like.

[0145] The system described in this specification rep-

resents a whole facility composed of a plurality of devices.

**[0146]** According to the entrance administration equipment of this invention, the information stored in the portable communication terminal, which is necessary after cutting the power of the portable communication terminal can be printed on a predetermined media, so that the information necessary after passing the entrance administration equipment is not necessary to be taken from the portable communication terminal.

**[0147]** According to the entrance managerial system of this invention, an entrance process can be executed by communicating information between the entrance administration equipment and the portable communication terminal. As a user enters inside of the entrance administration equipment, the power of the portable communication terminal can be automatically cut, and the information stored in the portable communication terminal which is necessary after cutting the power of the portable communication terminal can be printed on a predetermined media, so that the information necessary after passing the entrance administration equipment is not necessary to be taken from the portable communication terminal later.

**[0148]** While this invention has been described and illustrated with respect to certain embodiments which give satisfactory results, it will be understood by those skilled in the art, after understanding the purpose of the invention, that various other changes and modifications may be made without departing from the spirit and scope of the invention, and it is therefore, intended in the appended claims to cover all such changes and modifications.

## Claims

1. An entrance administration equipment, comprising  
     first transmitter (11) for transmitting a transmission command of first information representing visitor information to a portable communication terminal (21),  
     receiver (11) for receiving said first information from said portable communication terminal (21),  
     determining unit (31) for determining based on said first information received by said receiver (11) whether or not a user carrying said portable communication terminal (21) is allowed to enter,  
     printer (13) for printing second information on a predetermined media based on the first information received by said receiver (11) when said determining unit (31) determines that said user is allowed to enter, and  
     second transmitter (11) for transmitting to said portable communication terminal (21) a control signal for cutting power of said portable communication terminal (21).

2. An entrance administration equipment according to claim 1, in which said second information includes information necessary after cutting the power of said portable communication terminal (21) which is included in said first information.
3. An entrance administration equipment according to claim 1, in which said first and second information includes a seat number.
4. An entrance administration equipment according to claim 1, further comprising notifying unit (33) for notifying that said user is not allowed to enter.
5. An entrance administration equipment according to claim 1, further comprising controlling unit (39) for controlling a closing motion of a door (12) to limit passing of said user, in which said controlling unit (39) controls the closing motion of said door (12) based on determination results by said determining unit (31).
6. An entrance administration equipment according to claim 1, further comprising storing unit (35) for storing information with respect to said user who is allowed to enter, in which said determining unit (31) refers to information with respect to said user stored by said storing unit (35) and determines whether or not said user carrying said portable communication terminal (21) is allowed to enter.
7. An entrance administration equipment according to claim 1, further comprising storing unit (36) for storing the information of said user who is determined to enter by said determining unit (31).
8. An entrance administration equipment according to claim 1, in which said second transmitting unit (11) transmits to said communication terminal (21) a control signal for cutting power of a communicating function in said portable communication terminal (21) instead of the control signal for cutting the power of said portable communication terminal (21).
9. An entrance administration system including an entrance administration equipment (1) installed at an entrance to be entered by a user to a predetermined location and a portable communication terminal (21) carried by said user,  
     said entrance administration equipment (1), comprising  
         first transmitter (11) for transmitting a transmission command of first information representing visitor information to a communication terminal (21),  
         first receiver (11) for receiving said first information from said portable communication terminal (21),

determining unit (31) for determining based on said first information received by said first receiver (11) whether or not said user carrying said portable communication terminal (21) is allowed to enter,

5

printer (13) for printing second information on a predetermined media based on the first information received by said first receiver (11) when said determining unit (31) determines that said user is allowed to enter, and

10

second transmitter (11) for transmitting to said portable communication terminal (21) a control signal for cutting power of said portable communication terminal (21), and said portable communication terminal (21), comprising

15

storing unit (81A) for storing said first information,

second receiver (85) for receiving a transmission command of said first information stored in said storing means (81A) from said entrance administration equipment (1),

20

third transmitter (85) for transmitting said first information stored in said storing unit (81A),

third receiver (85) for receiving said control signal for controlling the power from said entrance administration equipment (1), and

25

controller (81) for controlling the power based on said control signal received by said third receiving means (85).

30

35

40

45

50

55

FIG. 1






FIG. 2



ENTRANCE ADMINISTRATION EQUIPMENT 1

FIG. 3



SHORT DISTANCE COMMUNICATION UNIT 11



**FIG. 4**60  
S

AIR LINE	ABC COMPANY
FLIGHT NUMBER	M402
SEAT NUMBER	L10-C3
PASSENGER	MR. THOMAS J.
DEPARTURE TIME	10:30
ARRIVAL TIME	12:45

FIG. 5




FIG. 6






FIG. 7





Europäisches Patentamt  
European Patent Office  
Office européen des brevets



(11) **EP 1 215 632 A3**

(12) **EUROPEAN PATENT APPLICATION**

(88) Date of publication A3:  
12.11.2003 Bulletin 2003/46

(51) Int Cl.7: **G07C 9/00**

(43) Date of publication A2:  
19.06.2002 Bulletin 2002/25

(21) Application number: **01129260.4**

(22) Date of filing: **12.12.2001**

(84) Designated Contracting States:  
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU  
MC NL PT SE TR**  
Designated Extension States:  
**AL LT LV MK RO SI**

- Yuji, Taketoshi, c/o Omron Corp., 801 Shimogyo-ku, Kyoto-shi, Kyoto 600-8530 (JP)
- Amehiko, Iki, c/o Omron Corp., 801 Shimogyo-ku, Kyoto-shi, Kyoto 600-8530 (JP)

(30) Priority: **14.12.2000 JP 2000379793**

(71) Applicant: **Omron Corporation**  
**Kyoto-shi, Kyoto 600-8530 (JP)**


(74) Representative: **Käck, Jürgen**  
**Kahler Käck Mollekopf**  
**Patentanwälte**  
**Vorderer Anger 239**  
**86899 Landsberg (DE)**

(72) Inventors:  
• **Tsuyoshi, Fujiwara, c/o Omron Corp., 801 Shimogyo-ku, Kyoto-shi, Kyoto 600-8530 (JP)**

(54) **Entrance administration equipment and system thereof**

(57) When an entrance administration equipment (1) detects an approaching user, it transmits a communication trigger command to a portable telephone (21), which is owned by the approaching user. When it receives a response signal from the portable telephone (21), it transmits a transmitting command of embarkation person information. When it receives the embarkation person information from the portable telephone (21), it executes an authentication process. When the embarkation person information does not coincide with data of the embarkation-scheduled person database, an entrance administration equipment (1) displays a message of a failure of the authentication process and doses a door (12). When the authentication process is succeeded, the entrance administration equipment (1) records the embarkation person information, opens the door (12), issues a ticket with printed embarkation person information, and transmits a control signal for turning off power of the portable telephone to the portable telephone (21).

**FIG. 1**



**EP 1 215 632 A3**



European Patent  
Office

## EUROPEAN SEARCH REPORT

Application Number  
EP 01 12 9260

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
Y	US 5 565 857 A (LEE KWANG-SIL) 15 October 1996 (1996-10-15) * abstract * * column 3, line 31 - column 4, line 18 * * column 5, line 60 - column 7, line 54 * * column 14, line 55 - column 17, line 14; figures 1-3,5-21,25 * ---	1-9	G07C9/00
Y	WO 99 55102 A (ISRAELI GIL ;TE ENI BEN (IL); NETLINE COMMUNICATIONS TECHNOL (IL)) 28 October 1999 (1999-10-28) * page 3, line 21 - page 5, line 11 * * page 20, line 22 - page 21, line 6 * * figure 2 * ---	1-9	
A	WO 98 35333 A (CASIO COMPUTER CO LTD ;TAGI MINORU (JP)) 13 August 1998 (1998-08-13) * abstract * * page 1, line 26 - page 3, line 10 * * page 7, line 25 - page 8, line 8 * * page 9, line 9 - page 10, line 28 * * page 11, line 29 - page 12, line 23 * * page 13, line 30 - page 14, line 2 * * page 18, line 13-23 * * page 19, line 14-19 * * figures 2,3,7 * ---	1-9	TECHNICAL FIELDS SEARCHED (Int.Cl.7)  G07C G07B G07F H04Q
A	US 6 112 989 A (SHELDON DUNSTAN P) 5 September 2000 (2000-09-05) * abstract * * column 3, line 65 - column 4, line 9 * --- -/--	1-3,9	
The present search report has been drawn up for all claims			
Place of search <b>THE HAGUE</b>		Date of completion of the search <b>17 September 2003</b>	Examiner <b>Pañeda Fernández, J</b>
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document	

EPO FORM 1503 03.02 (P04C01)

BEST AVAILABLE COPY



European Patent  
Office

# EUROPEAN SEARCH REPORT

Application Number  
EP 01 12 9260

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
A	WO 00 62260 A (LAUPER ERIC ;RITTER RUDOLF (CH); SWISSCOM AG (CH)) 19 October 2000 (2000-10-19) * abstract * * page 3, line 1 - page 4, line 7 * * page 4, line 22-31 * * page 9, line 24 - page 11, line 22 * * page 13, line 17 - page 14, line 14 * ---	1-9	
A	EP 0 913 979 A (BOSCH GMBH ROBERT) 6 May 1999 (1999-05-06) * abstract * * column 1, line 31 - column 2, line 14 * * column 2, line 44 - column 3, line 6 * * column 3, line 56 - column 4, line 20 * * column 5, line 48-58 * -----	1,2,8,9	
The present search report has been drawn up for all claims			TECHNICAL FIELDS SEARCHED (Int.Cl.7)
Place of search THE HAGUE		Date of completion of the search 17 September 2003	Examiner Pañeda Fernández, J
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons &amp; : member of the same patent family, corresponding document</p>			

EPO FORM 1503 03/02 (P04C01)

BEST AVAILABLE COPY

# ANNEX TO THE EUROPEAN SEARCH REPORT ON EUROPEAN PATENT APPLICATION NO.

EP 01 12 9260

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on  
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

17-09-2003

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5565857 A	15-10-1996	KR 9705637 B1	18-04-1997
		AT 153202 T	15-05-1997
		AU 658459 B2	13-04-1995
		AU 2896992 A	07-06-1993
		BR 9205419 A	19-04-1994
		CA 2098594 A1	01-05-1993
		DE 69219756 D1	19-06-1997
		DE 69219756 T2	18-12-1997
		EP 0565685 A1	20-10-1993
		HU 65528 A2	28-06-1994
		JP 6511097 T	08-12-1994
		WO 9309621 A1	13-05-1993
		RU 2178917 C2	27-01-2002
		US 5475377 A	12-12-1995
		CN 1086284 A , B	04-05-1994
		KR 225912 B1	15-10-1999
WO 9955102 A	28-10-1999	AU 3343799 A	08-11-1999
		EP 1074156 A1	07-02-2001
		WO 9955102 A1	28-10-1999
WO 9835333 A	13-08-1998	JP 10222057 A	21-08-1998
		JP 10320597 A	04-12-1998
		CN 1216132 A	05-05-1999
		CN 1216132 T	05-05-1999
		EP 0901676 A1	17-03-1999
		WO 9835333 A1	13-08-1998
		US 6473790 B1	29-10-2002
		US 2003018743 A1	23-01-2003
US 6112989 A	05-09-2000	NONE	
WO 0062260 A	19-10-2000	WO 0062260 A1	19-10-2000
		AU 763847 B2	31-07-2003
		AU 2919499 A	14-11-2000
		CA 2368377 A1	19-10-2000
		EP 1166238 A1	02-01-2002
		JP 2002541602 T	03-12-2002
		NO 20014669 A	26-09-2001
EP 0913979 A	06-05-1999	DE 19748054 A1	12-05-1999
		EP 0913979 A2	06-05-1999

EPO FORM P449

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

BEST AVAILABLE COPY